



**Plasma Block® Configuration Options - Summary Sheet**

| Air or Water cooled | Ozone output (grams) | Block version | Voltage    | Phase | Wattage *4 | Control board | Oxygen pressure | Oxygen flow | Chassis | Inlet/Outlet fittings |
|---------------------|----------------------|---------------|------------|-------|------------|---------------|-----------------|-------------|---------|-----------------------|
| PBA                 | 10                   | E1            | Univ       | 1Ø    | 150        | DAT           | 5-100 psi       | 3-10 lpm    | Std/Alt | *1                    |
| PBA                 | 20                   | E1            | Univ       | 1Ø    | 200        | DAT           | 5-100 psi       | 3-10 lpm    | Std/Alt | *1                    |
| PBA                 | 30                   | A1            | 120 or 240 | 1Ø    | 250        | SSD or DAT    | 5-86 psi        | 3-20 lpm    | Std     | *3                    |
| PBA                 | 45                   | D1            | 120 or 240 | 1Ø    | 440        | SSD or DAT    | 5-100 psi       | 3-15 lpm    | Std/Alt | *1                    |
| PBA                 | 60                   | B1            | 120 or 240 | 1Ø    | 500        | SSD or DAT    | 5-86 psi        | 3-20 lpm    | Std     | *3                    |
| PBA                 | 120                  | C1            | 240        | 1Ø    | 1000       | SSD or DAT    | 5-98 psi        | 3-30 lpm    | Std     | *3                    |
| PBA                 | 250                  | G1            | 230        | DC    | 2000       | DAT           | 5-100 psi       | 0-80 lpm    | Std     | *2                    |
| PBW                 | 150                  | C1            | 240        | 1Ø    | 2000       | SSD or DAT    | 5-98 psi        | 3-40 lpm    | Std     | *3                    |
| PBW                 | 300                  | C1            | 240        | 3Ø    | 2400       | SSD or DAT    | 5-98 psi        | 3-60 lpm    | Std     | *1                    |
| PBW                 | 350                  | F1 or F2*     | 230        | DC    | 2000       | DAT           | 5-100 psi       | 0-80 lpm    | Std     | *2                    |
| PBW                 | 450                  | C1            | 240        | 3Ø    | 3600       | SSD or DAT    | 5-98 psi        | 3-90 lpm    | Std     | NA                    |

\*1 - none, 1/4, 3/8, other      \*2 - none, 1/2, 3/8, other      \*3 - none, 1/4, 3/8, 8mm, 10mm, other

\*4 Units can be configured for lower wattage / less output (consult the factory)

F1 = gas 1/2" water 3/8"      F2 = manifold style porting

All Plasma Block® units are shipped with a Model number and Configuration label that includes the following information about the unit.

|   |   |
|---|---|
| <p><b>Model (example)</b><br/> <b>PBA-30g-A1-120v-1Ø-250w-D21</b></p> | <p><b>Configuration (example)</b><br/> <b>10psi-8 Lpm-C1-1/4S-1/4</b></p> |
|---|---|