

Plasma Block® Configuration Options - Summary Sheet

Air or Water cooled	Block version	Voltage	Phase	Ozone output (grams) @ 5% wt	Wattage *4	Control board	Oxygen pressure	Oxygen flow	Chassis	Inlet/Outlet fittings
PBA	E1	Univ	1Ø	10	137	D31	5-100 psi	3-10 lpm	Std/Alt	*1
PBA	E1	Univ	1Ø	20	245	D31	5-100 psi	3-10 lpm	Std/Alt	*1
PBW	I1	Univ	1Ø	26	245	D31				
PBA	A1	120 or 240	1Ø	30	250	D11 or D21	5-86 psi	3-20 lpm	Std	*3
PBA	D1	120 or 240	1Ø	50	400	D11 or D21	5-100 psi	3-15 lpm	Std/Alt	*1
PBA	B1	120 or 240	1Ø	60	500	D11 or D21	5-86 psi	3-20 lpm	Std	*3
PBD*	B1	120 or 240	1Ø	60	500	D11 or D21				
PBA	J1	240	1Ø	70	700	D21	5-100 psi	3-20 lpm	Std/Rack	*1
PBA	C1	240	1Ø	120	1000	D11 or D21	5-98 psi	3-30 lpm	Std	*3
PBA	K1	240	1Ø	140	1400	D21				
PBW	C1	240	1Ø	150	1200	D11 or D21	5-98 psi	3-40 lpm	Std	*3
PBW	C1	240	3Ø	300	2400	D11 or D21	5-98 psi	3-60 lpm	Std	*1
PBW	C1	240	3Ø	450	3500	D11 or D21	5-98 psi	3-90 lpm	Std	*1

*1 - none, 1/4, 3/8, other
 *2 - none, 1/2, 3/8, other
 *3 - none, 1/4m, 3/8, 8mm, 10mm, other
 *4 - Units can be configured for lower wattage / less output (consult the factory)
 F1 - gas 1/2" water 3/8 F2 - manifold style porting

All Plasma Block® units are shipped with a Model number label and if space permits, a configuration label.

